



# Quick Grip

Multi-Surface Building Envelope Adhesive

## Product Information Sheet

Poly Wall® Building Solutions is an innovator of high-quality, cost-effective, engineered building materials. We stand behind our brand promise — **Moisture and Air Stop Here®**. Visit our website at [www.poly-wall.com](http://www.poly-wall.com) for the full array of products.

### DESCRIPTION

Poly Wall's STA'-PUT® Quick Grip is an industrial-grade aerosolized adhesive in a portable spray system. Quick Grip is formulated to adhere protection courses, drainage composites, rigid insulation, sheet air & vapor barrier membranes, sheet waterproofing membranes, and sheet thru-wall flashings to a variety of substrates. It contains no chlorinated solvents and offers an excellent alternative to methylene chloride-based products. Quick Grip provides a fast and economical solution to most building envelope component adhesive requirements.

### ADVANTAGES

- Aggressive grab tack
- Quick dry time
- No clean-up or maintenance
- Very long working time
- Can be used as a primer or an adhesive
- Excellent adhesion to many substrates

### APPROVED EQUIPMENT

All items listed here that make up the Quick Grip Adhesive approved equipment are required for proper use and are sold individually by Poly Wall.

#### Surface Preparation:

- Spray gun: SG200
- Spray Tip: ST9502
- Hoses: MH973 (12')

### DIRECTIONS FOR USE

- Use only after careful consideration of the warnings, directions, and first aid instructions given. Do not thin.
- Surfaces to be bonded should be clean, dry and free of any dust, loose paint, wax, moisture, dirt, grease, oil, rust, or other contaminants.
- For best results, adhesive and materials to be bonded should be 60°F (15.6°C) to 95°F (35°C) during application.
- Before initial use securely attach gun to hose, then hose to canister. Fully open canister valve; do NOT close valve until empty.
- Spraying from 8 to 12 inches away, apply a uniform coat of adhesive to one surface, allowing to coat evenly across the substrate. Some porous surfaces may require two coats. Do not allow adhesive to "puddle". Be sure to have sufficient coverage of the surfaces for the application. Use only approved equipment.
- Both surfaces must be allowed to dry before bonding. This will usually take from 1 to 3 minutes at 60°F (15.6°C) under normal conditions. Heat and humidity, or cold weather can cause longer drying times. Surfaces are dry if adhesive is tacky, but no adhesive transfers to the hand when touched.
- Complete the bond within 60 minutes (under normal conditions) after the adhesive is dry. If the two surfaces don't grab immediately when brought into contact, they have dried too long.
- Position coated surfaces carefully before putting them together since no shifting is possible once contact is made.
- Bring surfaces together and immediately apply firm pressure (30 psi) over entire surface working from the center to the edges.
- Do not use on some membranes and components. When in doubt, conduct compatibility testing on the product to be bonded before use.
- After initial assembly, leave the hose and gun attached to the canister with the valve open.
- The installed total coverage area is 1200-1400 sq. ft./canister.
- After safely releasing line pressure, detach gun and hose only when transferring to a new canister.
- Reattach gun and hose immediately.



\*Note: All items that make up the Quick Grip Adhesive approved equipment shown in this graphic are required for proper use and are sold individually by Poly Wall.

Property	Typical Value
Base	Synthetic Polymer
Solvent	Organic Solvent*
Shelf Life	1 year from date of manufacture**
Color	Clear
Flash Point	-156°F (-104°C)
Weight / Gallon	5.86 lbs. / gallon
VOC Content	471.3 g/L (EPA Method 24)
Open Time	60 minutes
Dry Time	2 - 5 minutes
Formaldehyde	No urea formaldehyde added during adhesive manufacturing

\*Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.  
 \*\*The shelf life for an unopened container of this adhesive stored at temperatures between 60°F (15.6°C) and 95°F (35°C) is 1 year from date of manufacture. Store out of direct sunlight in a cool, well-ventilated area. Avoid storing container directly on the floor or against an outside wall.

### SAFETY

Empty container remains hazardous until all flammable vapors, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions. Do not cut, puncture, or weld while hazard exists. Do not reuse empty container. Recycle, or dispose of, according to all federal, state, and local regulations. Follow solvent manufacturer's recommendations  
**KEEP OUT OF REACH OF CHILDREN FOR PROFESSIONAL OR INDUSTRIAL USE ONLY USE ONLY WITH APPROVED EQUIPMENT**

**LIMITED WARRANTY:** Poly Wall Building Solutions will replace F.O.B. Ennis, TX, any material with manufacturing defects which cause leaks for a period of 1 year from date of purchase. Poly Wall Building Solutions will not be liable for any other claims or damages, whether direct or indirect, including consequential damages or incidental damages.



**POLY WALL® BUILDING SOLUTIONS:**  
**Moisture and Air Stop Here®**  
 888-976-POLY (7659) • [www.poly-wall.com](http://www.poly-wall.com)



REV03/11/20